

SOLIDS AND STRIPES

Technical sheet



CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

GENERAL CHARACTERISTICS

Composition	100% Sunbrella solution dyed acrylic		
Weave	Canvas		ISO 7211-1
Finish	Water-repellent & Stain-proof		
Weight	260	g/m ²	ISO 3801
Width	137	cm	EN 1773
Roll length	50	ml	

FABRIC RESISTANCE

Oil-resistance properties	5		Class / 8	ISO 14419
Spray test	5		Class / 5	ISO 4920
Schmerber	200		mm	ISO 811
Seam slippage (180 N)	<3	<3	mm	ISO 13936-2
Elongation at break	33	26	%	ISO 13934-1
Stitching strength	42.9	51.1	daN	ISO 13935-2
Stability on 40 deg. C washing	±1	±1	%	ISO 5077
Tensile strength	160	90	daN/5cm	ISO 13934-1

COLOUR-FASTNESS

Colour fastness UV - indoor	8		Class / 8	ISO 105 B02
Colour fastness UV - outdoor - 1000h	4/5		Class / 5	ISO 105 B04
Colour fastness under dry friction	5		Class / 5	ISO 105X12
Colour fastness under wet friction	5		Class / 5	ISO 105X12
Colour fastness 40 deg. C washing	5		Class / 5	ISO 105 C06

USES

Guarantee	5	years
Recommended Uses	cushions, curtains, seating, shade sail, umbrella, roman blinds, Pergola	

CARE



This product's values may vary with a tolerance of ± 5%

Dickson-Constant SAS, [French limited-liability corporation] with capital of €12,640,000 - Metropolitan community of Lille business registration

10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France

Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - www.dickson-constant.com/en/UK

